

## Metro

### F49G07A35

#### Technical Design




Fixture Type

Project Name



#### Dimensions



#### Description

Wall and ceiling lamp with stainless steel structure. The LED strip can be set up to create direct or indirect light. The strip can be cut to measure.

#### Voltage

24Vdc

#### Dimmable

Remote Driver

#### Specs



DRY



#### Material

Stainless steel

#### Light source

LED 2 x 96W Strips  
3500K  
11520lm  
Cri >90

#### Notes

Requires (2) Remote Drivers (Not Included)  
Each Driver powers up to 16' max from each end of the fixture.  
Models available include: A55209 (120V / ELV Dim) or A55210 (120-277V / 0-10V Dim)  
Compatible with Lutron 96W HiLume Premier L3D0 24V Constant Voltage PWM 0.1% and Soft on / FadeToBlack

#### Included accessories

2 x 16' LED strips IP65 with 4' wire whips  
2 wall attachments  
10.3m (33' 7") metal strip

#### Weight Lamp






















Net: 5.51 lb

#### Packaging

Gross weight: 6.83 lb  
Volume: 0.67 ft<sup>3</sup>  
Number of boxes: 1

# Metro F49

## Other options

	code	electrification	technical info
	<b>F49 G01 A 35</b>	LED 24Vdc 1x96W 3000K 5760lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G02 A 35</b>	LED 24Vdc 1x96W 2700K 5760lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G05 A 35</b>	LED 24Vdc 1x96W 3500K 5760lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G06 A 35</b>	LED 24Vdc 1x96W 4000K 5760lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G03 A 35</b>	LED 24Vdc 2 x 96W 3000K 11520lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G04 A 35</b>	LED 24Vdc 2 x 96W 2700K 11520lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G07 A 35</b>	LED 24Vdc 2 x 96W 3500K 11520lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 G08 A 35</b>	LED 24Vdc 2 x 96W 4000K 11520lm Cri >90	 <b>DRY</b>  ACCESSIBLE SYSTEM
	<b>F49 Z07 A 35</b> Spare Wall Attachments	<b>F49 Z01 A</b> Wall to Ceiling Curve Bracket	<b>F49 Z05 A</b> Ceiling Anchor
	